

Living Wall

Parts List

3- 6 ½ ft long pipe

2- 20 in. long pipes

2 gray connector tubes

2 elbow tubes

1 6 ft. x 7ft. webbing

Zip ties

Ground staples

- 1. Select a sunny area behind your garden and measure a length between 12 and 18 in. from the ground pots.*
- 2. Take one of the long poles and attach an elbow to each end.*
- 3. Lay that pole at the 12 to 18 in distance from the ground pot making sure the elbows are pointed towards the ground pots.*
- 4. Depending on the size of your garden the position of the living wall should cover at least 2 ground pots.*
- 5. Marking the location where the elbows are on the ground tap the 2 short poles into the ground leaving at least 6 inches of the short poles above the ground.*
- 6. Lift the long pipe with the elbows off the ground, roll out the netting and attach the 6 ft long side to the netting by sliding zip ties over the pole. Leave net dangle until erected*
- 7. Slide gray connector tubes over the small pipes in the ground*
- 8. Slide the 2 remaining long pipes into the elbows.*
- 9. With someone helping lift the entire wall up and slide into the gray connector pipes.*
- 10. Now attach the netting on both sides with the zip ties. Leave the zip ties loose, you can tighten them later. The zip ties on the side poles can be about 18 in apart.*
- 11. Tap the ground clips starting and ending at the bottom of the netting.*
- 12. Attach the zip ties to the netting and around the sod clips. You may need 2 zip ties for more length if one doesn't reach the ground clip.*
- 13. Now that the Living Wall is erected you can go around the edges and tighten the zip ties.*